



SPRINGFIELD ARMORY. SAINTTM 5.56

SPECIFICATIONS

WEIGHT:	6lbs 11oz	TRIGGER GUARD:	BRAVO COMPANY TRIGGER GUARD
LENGTH:	35.5" FULLY EXTENDED / 32.25" COLLAPSED	PISTOL GRIP:	BRAVO COMPANY MOD 3
UPPER RECEIVER:	TYPE III HARD COAT ANODIZED AIRCRAFT GRADE 7075 T6 ALUMINUM FLAT TOP UPPER RECEIVER WITH FORWARD ASSIST AND M4 FEED RAMPS	HANDGUARD:	NEW, EXCLUSIVE BRAVO COMPANY, KEYMOD, PKMR
LOWER RECEIVER:	TYPE III HARD COAT ANODIZED AIRCRAFT GRADE 7075 T6 ALUMINUM LOWER RECEIVER WITH ACCU-TITE TM TENSION SYSTEM	BUTT STOCK:	BRAVO COMPANY 6 POSITION
BARREL:	16" HIGH QUALITY CHROME MOLY VANADIUM BARREL CHAMBERED IN 5.56 NATO WITH A 1:8 RH TWIST, MELONITE [®] TREATMENT APPLIED TO CHAMBER, BORE AND EXTERNAL SURFACES	BUFFER ASSEMBLY:	CARBINE "H" HEAVY TUNGSTEN BUFFER
GAS SYSTEM:	DIRECT IMPINGEMENT MID-LENGTH GAS SYSTEM WITH A .750 DIAMETER GAS BLOCK / FRONT SIGHT BASE	RECEIVER EXTENSION:	MIL-SPEC CARBINE RECEIVER EXTENSION MANUFACTURED FROM 7075 T6 TYPE III HARD ANODIZED ALUMINUM
TRIGGER:	SPRINGFIELD ARMORY [®] PROPRIETARY, ENHANCED NICKEL BORON COATED GI SINGLE STAGE TRIGGER	CHARGING HANDLE:	GI STYLE
SIGHTS:	SPRINGFIELD ARMORY [®] LOW PROFILE FLIP-UP, DUAL APERTURE REAR SIGHT, 1/2 MOA WINDAGE ADJUSTMENT	BOLT CARRIER GROUP:	M16 BCG W/ CARPENTER 158 STEEL BOLT, SHOT PEENED AND MAGNETIC PARTICLE INSPECTED TO ENSURE IT MEETS MIL-SPEC DURABILITY REQUIREMENTS
		MAGAZINE:	1 - 30 ROUND MAGPUL PMAG GEN M3